

MEA[®] DRAIN SUPREME

Polymer concrete systems

System overview

- EN 1000
- EN 1500
- EN 2000
- EN 3000
- ENS 2000
- ENS 3000
- ENS 3070
- ENS 4000



A15	B125	C250	D400	E600	F900
<ul style="list-style-type: none"> • Pedestrians • Cyclists • Green areas 	<ul style="list-style-type: none"> • Passenger car parking lots and parking decks • Delivery vans 	<ul style="list-style-type: none"> • Trucks • Hard shoulder • Verge 	<ul style="list-style-type: none"> • Roadways 	<ul style="list-style-type: none"> • Industrial areas 	<ul style="list-style-type: none"> • Special surfaces such as air traffic areas

MEA® DRAIN SUPREME

System overview



EN 1000



Clear width: 100 mm
Total width: 140 mm
Total height: from 150 to 305 mm

- Channel unit for a linear fall (base fall 0,5%) and without fall
- Also with integrated outlet connector
- Loading class A15 to F900

EN 1500



Clear width: 150 mm
Total width: 190 mm
Total height: 180/220/270/320 mm

- Channel unit for a stepped fall (0,5%) and without fall
- Also with integrated outlet connector
- Loading class A15 to F900

EN 2000



Clear width: 200 mm
Total width: 240 mm
Total height: 220/280/330/380 mm

- Channel unit for a stepped fall (5%) and without fall
- Also with integrated outlet connector
- Loading class A15 to F900

EN 3000



Clear width: 300 mm
Total width: 370 mm
Total height: from 390 to 490 mm

- Channel unit without fall
- Also with integrated outlet connector
- Loading class A15 to F900

ENS 2000



Clear width: 200 mm
Total width: 294 mm
Total height: 330 mm

- Channel unit without fall
- Also with integrated outlet connector
- Loading class A15 to D400

ENS 3000



Clear width: 300 mm
Total width: 394 mm
Total height: 400 mm

- Channel unit without fall
- Also with integrated outlet connector
- Loading class A15 to F900

ENS 3070



Clear width: 300 mm
Total width: 394 mm
Total height: 760 mm

- Channel unit without fall
- Also with integrated outlet connector
- Loading class A15 to F900

ENS 4000



Clear width: 400 mm
Total width: 494 mm
Total height: 465 mm

- Channel unit without fall
- Also with integrated outlet connector
- Loading class A15 to F900